

ShawContract®

Duality 4.5 X 9 Glossy

Style Number	CT81K
Composition	Porcelain
Tile Type	Subway Tile
Body Type	Glazed Porcelain
Finish	Glossy
Nominal Dimensions	4.5" x 9" 11.43 cm x 22.86 cm
Actual Dimensions	4.5" x 9.06" 11.43 cm x 23.02 cm
Overall Thickness	0.334" 8.5 mm
Edge Profile	Pressed
Country Of Origin	Spain
Installation Area	Walls
Retail Unit Of Measure	Sold by the box quantity

Packaging

Pieces per Carton	24
Area per Carton	6.89 ft²
Weight per Carton	23.7 lbs
Area per Pallet	702.78 ft²
Boxes per Pallet	102 boxes

Recommended Installation Method

Grout Joint Requirement: Minimum of 1/8"
Recommended to grout over pre-scored line.

Performance + Testing

Shade Variation	V3	
Breaking Strength (ASTM C648)	≥ 125 lbf	
Water Absorption (ASTM C373) %	≤ 0.50% (Impervious (Porcelain))	
Frost Resistance (ASTM C1026)	Resistant	
Chemical Resistance (ASTM C650)	Class A	
Stain Resistance (ISO 10545-14)	Class 5	
Wear Rating	*0 (Walls Only)	*Not suitable for floors. Use only on walls or vertical surfaces.

Areas of Application

Interior Walls/Backsplash	✓	Interior Wet Plus	
Interior Dry Floors		Exterior Wet Floors	
Interior Wet Floors		Exterior Walls	✓
Shower Floors		Oils / Grease	

Warranties

[1 Year Commercial Limited Warranty](#)

Available Colorways



100 Classic



106 Reset



375 Harmony



423 Heritage



506 Antique



675 Renew

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Additional Information

Per ANSI A326.3, a DCOF of ≥ 0.42 is recommended for tiles in commercial applications. Tiles with a DCOF < 0.42 are not recommended for wet or slippery areas. Contaminants like water, oil, or grease can increase slip risk—use caution when selecting products for such environments. For approved Areas of Application, please reference the chart above. For more information, visit www.tcnatile.com.

Not for use on ramps.

Due to natural variation in ceramic and porcelain tile, final selection should be based on actual product samples.

[Ceramic Porcelain Step By Step Installation](#)

[Maintenance Guidelines](#)