



# R | Entangle

## PRODUCT SPECIFICATIONS

<b>COLLECTION</b>	Interweave	
<b>STYLE NUMBER</b>	I622V	
	<b>US Units</b>	<b>Metric Units</b>
<b>OVERALL THICKNESS</b>	0.118 inches	3 mm
<b>EDGE PROFILE</b>	Squared Edge	
<b>FINISH</b>	ExoGuard®	
<b>INSTALLATION TYPE</b>	Dry Back	
<b>INSTALLATION</b>	Glue Down	
<b>RECOMMENDED ADHESIVE</b>	4200 (4 gal), 2200 (4 gal), 4252 (4 gal) or S150 SPRAY ADHS	

## Packaging

<b>PLANK SIZE</b>	18 inches W x 36 inches L	45.7 cm W x 91.4 cm L
<b>PIECES /BOX</b>	8	
<b>AREA /BOX</b>	36 sq ft	3.3 sq m
<b>WEIGHT /BOX</b>	37.21 lbs	16.9 kg

## Performance Testing

<b>STATIC LOAD / ASTM F970</b>	Passes (Modified), *1500 lbs
<b>RESISTANCE TO CHEMICALS / ASTM F925</b>	Passes
<b>RADIANT PANEL / ASTM E648</b>	Passes, Class I
<b>COEFFICIENT OF FRICTION (ASTM D2047, SLIP RESISTANCE)</b>	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

\*Results are based on a laboratory test and used for comparative purposes. Real life load limit may vary.

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

## Warranty

15 Year Commercial Limited.

Please visit [patcraft.com](https://patcraft.com) for the most current warranty information.

## Environmental Specifications

<b>EMBODIED CARBON (CRADLE TO GATE)</b>	7.45 kg CO <sub>2</sub> /m <sup>2</sup>
---	---

## Third Party Certifications

<b>HEALTH PRODUCT DECLARATION (HPD)</b>	1,000 PPM Disclosure
<b>ENVIRONMENTAL PRODUCT DECLARATION (EPD)</b>	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
<b>FLOORSCORE®</b>	Certified