

Feature Hexagon Taskworx® Tile

Style Number	H002X	
Collection	Auxiliary	
Product Type	Carpet Tile	
Construction	Standard	Data + Performance
Type of Manufacture	ISO 2424	tufted 1/12"   47.2 per 10cm
Aspect	ISO 2424	Level Loop
Dye Method	EN 994	100% Solution Dyed
Dimensions	EN 994	73.2 cm x 24.9 cm   20 tiles (4.25 m²) per box
Primary Backing	ISO 2424	Pet Non-Woven
Secondary Backing	ISO 2424	Taskworx® Tile   Polymer Modified Bitumen
Pile Fibre Composition	ISO 2424	Aquafil Polyamide 6
Total Thickness	ISO 1765	5.3 mm
Effective Pile Thickness	ISO 1766	2.1 mm
Total Mass	ISO 8543	3920 g/m²
Nominal Total Pile Mass	ISO 2424	450 g/m²
Effective Pile Mass	ISO 8543	259 g/m²
Pile Density	ISO 8543	0.122 g/cm³
Total Recycled Content		53% (pre-consumer 53%   post-consumer 0%)
Performance		
Number of Tufts	ISO 1763	184,000/m²   39 per 10 cm
Electrostatic Propensity	ISO 6356	≤ 2.0 kv (Stroll Test)
Use Classification	EN 1307	33 Commercial Heavy
Luxury Class	EN 1307	LC1
Dimensional Stability	EN 986	≤ 0.2%
Impact Sound Insulation	ISO 10140	21db
Sound Absorption Classification	ISO 354/11654	0.10 Aw
Thermal Resistance m² K/W	ISO 8302	0.046 M² K/W Tog 0.46
Dry Slip Resistance	ISO 13893	Pass / No Pulled Loops
Colour Fastness To Light	ISO 105-B02	>6
Flammability	EN 13501-1	Bfl-S1 (Adhered Testing)
Castor Chair	EN 985	≥2.4 Continuous USe
15 Year Commercial Limited Warranty subject to installation in full accordance with the manufacturer's instructions and a regular effective cleaning and maintenance programme. Second location warranties are available with the use of non-adhesive IOBAC Magtabs and Tabit accessories.		

Recommended Installation Method




Random



Monolithic

Product Transparency

Shaw Contract is dedicated to providing clients with a building chemistry that's safe and dependable. Working together, we will help you meet your goals as they pertain to material health. TaskWorx® products are Cradle to Cradle Certified® Bronze and assessed for impacts on human health and the environment. This product can be recycled. When it's time to replace, we can collect through our re-[TURN] scheme in EMEA.



## Coordinating Products

Carpet Tile: **Complement Hexagon Taskworx® Tile, Detail Hexagon Taskworx® Tile, Complement Taskworx® Tile, Detail Taskworx® Tile, Feature Taskworx® Tile**

## Material Health & Environmental Certifications

Cradle to Cradle Certified®

Environmental Product Declaration (EPD)

Environmental Guarantee\*

ISO 9001

Country of Origin\*\*

BREEAM Contribution Credit

**Bronze Level (Version 3.1)**

**3rd Party Certified in Accordance with ISO14044, ISO14025 & EN15804**

**Take Back Policy Offered For All Taskworx Products**

**Certified**

**United Kingdom**

**Certificate of Approval**

**Schools/Offices/Health/Industrial Shed**

**Retail**

## WELL V2 Contribution Credit

X08 Hazardous Material Reduction

Part 1: Limit Hazardous Materials Optimization

**C2C Bronze Level (Version 3.1)**

X10 Volatile Compound Reduction

Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization

**C2C Bronze Level (Version 3.1)**

X10 Volatile Compound Reduction

Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization

**C2C Bronze Level (Version 3.1)**

X11 Long Term Emissions Control

Part 2: Flooring Optimization

**M1> Emissions Class For Building Material**

X13 Enhanced Material Precaution

Part 1: Select Optimized Materials Optimization

**C2C Bronze Level (Version 3.1)**

X14 Material Transparency

Part 1: Promote Ingredient Disclosure Optimization

**C2C Bronze Level (Version 3.1)**

## Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization

Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)

**3rd Party Certified in Accordance with ISO14044, ISO14025 & EN15804**

MR Credit: Building Product Disclosure and Optimization

Material Ingredients - Option 1: Material Ingredient Reporting

**C2C Bronze Level (Version 3.1)**

MR Credit: Building Product Disclosure and Optimization

Material Ingredients - Option 2: Material Ingredient Optimization

**C2C Bronze Level (Version 3.1)**

EQ Credit: Low Emitting Materials

Option 1: Product Category Calculations

**Certified**

## Air Quality

Indoor Air Comfort Gold

M1

**Certified**

**Certified**

## Memberships

WGBC Framework

UKGBC

Emirates Green Building Council

Chemsec









**WGBC Framework**

**UKGBC**

**Emirates Green Building Council**

**Chemsec**

Light Reflectance Value

					
Smoke Spring 83326 LRV 11.7 (range 8.6 - 18.0)   L* 40.67 (range 35.13 - 49.44)	Smoke Azure 83486 LRV 10.2 (range 8.6 - 12.3)   L* 38.26 (range 35.11 - 41.75)	Smoke Black 83505 LRV 7.3 (range 4.7 - 9.7)   L* 32.45 (range 25.89 - 37.26)	Pebble Ash 83535 LRV 10.8 (range 6.4 - 15.8)   L* 39.23 (range 30.44 - 46.67)	Smoke Ice 83536 LRV 12.1 (range 16.6 - 82.3)   L* 41.40 (range 34.5 - 47.74)	Pebble Flint 83549 LRV 6.5 (range 4.2 - 8.7)   L* 30.57 (range 24.16 - 35.34)
					
Pebble Coral 83866 LRV 8.4 (range 6.6 - 10.1)   L* 34.84 (range 30.95 - 38.02)	Pebble Blossom 83870 LRV 8.6 (range 7.3 - 10.8)   L* 35.19 (range 32.37 - 39.25)				

Additional Information

\*\*Manufactured in ISO 9001 certified facility. Meets or exceeds all local and national regulations in country of manufacture.

[Installation Guidelines](#)

[Maintenance Guidelines](#)

[15 Year Commercial Limited warranty](#)

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

